

Alarm Flashers



Radio Transmission

The Alarm Flasher provides a local alarm to enable quick alerting of temperature outages or connectivity problems.

Each Alarm Flasher has an Audible Alarm facility that can be deactivated if not required.

Models

AL1 – Alarm Flasher Wired

The AL1 Alarm Flasher is a wired alarm that plugs into (and is powered from) the Network Controller and so will be located beside the Network Controller.

AL3 – Alarm Flasher Wireless

The AL3 Alarm Flasher is a wireless alarm that communicates via RF signal from the Network Controller and so can be placed anywhere in the system network area.

Flasher Specification	
Bulb:	XENON Strobe Blue
Current Rating:	160mA
Input:	12VDC 1A

AL1 Specification	
Product Code:	AL1
Size:	W 70mm, H 58mm, D 95mm
Weight:	131g.

AL3 Specification	
Product Code:	AL3
Radio Frequency Band:	916MHz (USA) ; 868MHz (Europe).
Line of sight range:	up to 100m
Reprogrammability:	Fully Reprogrammable over RF
Power Supply:	12VDC 1A Mains Adapter (supplied)
Backup Battery:	1 x Pack 4.8V NiMH (pack of 4 x 1.2v AA Size).
Size:	W147mm, H 168mm, D 65mm
Weight:	427g.